



Original may vary from picture

Main features of the machine:

- Compact Scaler for holding a hydraulic hammer for use in underground mining
- Working height, max.: 10,0 m

Operating conditions:

- Operating temperature: -20°C *to +40°C
 - Permissible longitudinal gradient: max. 35%
 - Operating altitude above sea level: < 1.500 m
- * note cold start limit temperature of the diesel engine

Chassis:

- Divided chassis with articulated steering
 - Rigid mounted front axle and oscillating rear axle
 - Angel of oscillation: +/- 8°
 - Automatic lock function of the oscillation by swiveling the boom > ± 15°
 - Operating weight: 13.000 kg*
 - Payload, max: 300 kg
 - Permissible front axle load: 9.500 kg
 - Permissible rear axle load: 7.000 kg
- * depending on selected options

Hermann Paus Maschinenfabrik GmbH, Siemensstr. 1 – 9, 48488 Emsbüren, Germany

Tel.: +49-5903-707-0, Fax.: -33, email: info@paus.de, internet: www.paus.de

© Hermann Paus Maschinenfabrik GmbH

Boom:

- Telescopic boom with two stages and hydraulic swivel function
 - All bearings are made of wear-resistant material
 - Lift cylinders with safety check valves
 - Robust wiper to protect telescopic boom against dirt
 - Rock protector at the boom to protect hydraulic fittings
 - Rock deflector on top of the boom
-

Scraper blade:

- hydraulic lift
 - mechanical parallel guide
-

Diesel engine:

- Manufacturer: Deutz
 - Type: BF 4M 2012 C
 - Exhaust stage: EU stage II / EPA Tier 2
 - Power: 98 kW at 2.300 min⁻¹
 - Generator: 28 V, 80 A
 - Starter: 24 V, 4.0 kW
 - Cooling system: liquid cooled
 - Cold start limit temperature: -15°C
 - Fuel prefilter and fuel fine filter with water separator
-

Exhaust system:

- Catalyzer with measuring points before and after
 - Silencer
-

Intake system:

- Dry air filter with pre-filter
-

Fuel system:

- Fuel tank capacity: 150 l
 - Electric level indicator
-

Driveline:

- Hydrostatic propel drive
 - Gears and driving direction can be changed under load
 - All wheel drive
 - Driving performance:
 - o Driving speed forward and reverse: 18 km/h
 - o Tow capacity: 53 kN
-

Axles:

- Manufacturer: DANA
 - Type: 123
 - Differential: 100%
-

Service brake:

- 2 circuit hydraulically operated brake, actuated by brake pedal
- In the axle housings located oil-immersed multiple disc brakes

Parking brake:

- Spring-applied, hydraulically released parking brake
- SAHR – Brake

Auxiliary brake:

- One circuit of the service brake

Tires:

- Dimension, Single tired: 15,5x25
- Foamed

Hydraulic system:

- Tank capacity: 1x65 l, 1x90 l
- Two separate hydraulic circuits, one for hammer hydraulic and the other for driving and working hydraulic
- Inspection glasses for Min/Max indication
- Temperature sensor
- Electric level indicator, control of minimum level
- All screwing's in DIN type

Steering:

- Hydraulic-articulated steering with two double-acting hydraulic cylinders
- Steering wheel
- Emergency steering

Electric system:

- Operating voltage: 24 V
- Battery: 2 x 12 V, 74 Ah
- main switch
- Emergency stop button, 1x in the drivers stand
- Reversing signal

Lighting:

- 2 front headlights with high beam, low beam, parking light and indicator
 - 2 rear lights with taillight, brake light, rear beam and indicator
 - 2 LED-working lights at cabin roof front
 - 2 LED-working lights at cabin roof rear
 - 1 LED-working light at telescopic boom
 - 1 LED flash light (yellow)
-

Driver's compartment:

- Open drivers stand:
 - ROPS/FOPS proofed
 - Entrance from left, emergency exit on the right
 - Safety glass on front, rear and in the roof
 - Wipers and washing plant on front and roof window
 - Hinged rock protection grid on front and roof windows
 - 2 side mirrors
 - Control of hydraulic hammer with foot switch or joystick
 - All switches and controls placed in the range of the operator
- Driver's seat:
 - with lap belt
 - Synthetic leather cover
 - Adjustment of back part and seating

Finish:

- RAL 1007 / 7016

Accessories and equipment (included):

- 1 Articulation joint lock
- 1 central grease bar
- 1 hand-held fire extinguisher Total PK 10 / BuT 10
- 2 chocks
- 1 Tool kit with bag
- 1 Safety helmet and ear protection
- 1 triangular safety reflector
- 1 first-aid kit

Documentation:

- 2 operating instructions, 1 in printed form in the document box on the vehicle
- Spare part list in electronic form

Options

Diesel engine:

- Manufacturer: Deutz
- Type: TCD 2012 L04 2V
- Exhaust stage: EU Stage III A / EPA Tier 3 (MSHA certification)
- Power: 93 kW at 2.400 rpm
- Generator: 28 V, 80 A
- Cold start limit temperature: -10°C

Diesel engine:

- Manufacturer: Deutz
 - Type: TCD 4.1
 - Exhaust stage: EU Stage V / EPA Tier 4f
 - Power: 105 kW at 2200 rpm
 - Generator: 28 V, 95 A
 - Cold start limit temperature: -10°C
-

Hydraulic Hammer:

- Special hydraulic hammer for scaling operation
- Manufacturer: NPK
- Type: PH-2TS
- Operating weight: 260 kg
- frequency: 500 – 1200 min⁻¹
- Central lubrication system for hydraulic hammer
- moil chisel, long version

Hydraulic hammer:

- Manufacturer: Atlas Copco
- Type: SB 202
- Operating weight: 200 kg
- frequency: 850 – 1800 min⁻¹

Hydraulic hammer:

- Manufacturer: Atlas Copco
 - Type: SB 302 SC
 - Operating weight: 304 kg
 - frequency: 950 – 1250 min⁻¹
-

Dust suppression system:

- Water tank 80 l
 - Water pump
 - Nozzle placed at hydraulic hammer
-

Air pressurization of hammer:

- compressor
 - Air pressurization of hammer case to avoid contamination
-

Driver's cap:

- Closed drivers compartment with ventilation and heating
 - Air conditioning unit
-

Tires:

- Spare wheel
-

Screwing's:

- JIC-screwing's
-

Remote control:

- Remote control complete
 - Remote control "plug in"
-

Fire extinguishing system:

- HRD fire extinguishing with manual release
 - HRD fire extinguishing with automatic release
-

Additional options:

- Automatic central lubrication
 - Electrical connectors with optimized corrosion protection through internal grease filling and external sealing with self-welding tape
 - 1 hand-held fire extinguisher made from ANSUL
 - Service packages for 2.000 operating hours
 - Service packages for 3.000 operating hours
-

Further equipment and options on request
